

Fuji® Dex 740/760 OPC Unit

Oasis Imaging Products Inc. Technical Support (888) 627- 6555

Reference Information:

OEM PN: UA930-861
 OEM Yield: 19,000 (5% coverage)

Printer Compatibility:

Fuji Dex 720, 740, 760
 Konica Fax 860L/ 865L

Recommended Tools:

Phillips head screwdriver

Approximate Remanufacturing

Time: 20 min.

Instructions:

1. Remove 2 screws from top (Fig. 1) and remove corona wire assembly.
2. Remove end cap by unhooking the two hidden clips. Remove two screws (Fig. 2).
3. Remove hidden screw (Fig. 3). Turn auger assembly to the right (Fig. 4) to expose the drum axle.
4. Clean all contacts and remove the axle.
5. Remove screw from remaining drum axle bushing (Fig. 5). First remove bushing then remove OPC.
6. Clean and inspect the OPC. Replace if necessary.
7. With a Phillips screwdriver, remove the 2 screws from back panel.
8. Vacuum out any waste toner. Remove the 2 screws securing the wiper blade. Clean and inspect the wiperblade. Replace if necessary.
9. Replace the wiperblade and back panel.
10. Replace the OPC and attach gear hub and axles.
11. Replace the waste auger and 3 screws. Attach cover plate.
12. Clean both corona wires. Attach top corona wire assembly and secure with screws.




Figure 1




Figure 2




Figure 3




Figure 4




Figure 5